

## DVM - 2-Leiter-Systeme

Verbleibende Anschlussleistung ab Verteiler (kW)		Kältemittelverteiler	Ø Rohrquerschnitt (mm) ab Verteiler		Ø Rohrquerschnitt (Zoll) ab Verteiler	
Min	Max		Flüssig	Sauggas	Flüssig	Sauggas
	15,0	MXJ-YA1509	9,52	15,88	3/8	5/8
>15,0	23,2			19,05		3/4
>23,2	29,0	MXJ-YA2512	12,70	22,22	1/2	7/8
>29,0	40,6			25,40		1
>40,6	46,4	MXJ-YA2815	15,88	28,58	5/8	1 1/8
>46,4	69,6					
>69,6	98,6	MXJ-YA3119	19,05	31,75	3/4	1 1/4
>98,6	139,2	MXJ-YA3819	38,10	1 1/2		
>139,2		MXJ-YA4422	22,22	44,45	7/8	1 3/4

## DVM - 3-Leiter-Systeme mit Wärmerückgewinnung

Verbleibende Anschlussleistung ab Verteiler (kW)		Kältemittelverteiler		Ø Rohrquerschnitt (mm) ab Verteiler			Ø Rohrquerschnitt (Zoll) ab Verteiler		
Min	Max	Flüssig + Sauggas	Heißgas	Flüssig	Sauggas	Heißgas	Flüssig	Sauggas	Heißgas
	15,0	MXJ-YA1509	MXJ-YA1500	9,52	15,88	15,88	3/8	5/8	5/8
>15,0	23,2				19,05			3/4	
>23,2	29,0	MXJ-YA2512	MXJ-YA2200	12,70	22,22	22,22	1/2	7/8	7/8
>29,0	40,6				25,40			1	
>40,6	46,4	MXJ-YA2815	MXJ-YA2500	15,88	28,58	25,40	5/8	1 1/8	1
>46,4	69,6								
>69,6	98,6	MXJ-YA3119	MXJ-YA2800	19,05	31,75	28,58	3/4	1 1/4	1 1/8
>98,6	139,2	MXJ-YA3819	MXJ-YA3100		38,10			31,75	1 1/2
>139,2		MXJ-YA4422	MXJ-YA3800	22,22	44,45	38,10	7/8	1 3/4	1 1/2

Techn. Änderungen und Irrtum vorbehalten.



WE TURN ON TOMORROW

Exklusiv-Partner für Deutschland



## DVM - 2-Leiter-Systeme

Leistung	Verteiler z. Verbinden einzelner Module		Ø Rohrquerschnitt (mm)				Ø Rohrquerschnitt (Zoll)							
(KW)	Flüssig & Sauggas		Flüssig	Sauggas		Ölausgleich	Flüssig	Sauggas		Ölausgleich				
22,4	MXJ-T3819	X	9,52	19,05		6,35	3/8	3/4		1/4				
28,0				22,22				7/8						
33,6			12,70	25,40			1/2	1						
39,2				15,88				28,58			5/8	1 1/8		
44,8			19,05		31,75			3/4				1 1/4		
50,4					38,10							1 1/2		
56,0			22,22		44,45		7/8	1 3/4						
61,6			MXJ-T4422	X	22,22		44,45		6,35		7/8	1 3/4		1/4
67,2														
72,8~84,0														
89,6~95,2														
100,8~134,4														
>140,0														

## DVM - 3-Leiter-Systeme mit Wärmerückgewinnung

Leistung	Verteiler z. Verbinden einzelner Module		Ø Rohrquerschnitt (mm)				Ø Rohrquerschnitt (Zoll)							
(KW)	Flüssig & Sauggas	Heißgas	Flüssig	Sauggas	Heißgas	Ölausgleich	Flüssig	Sauggas	Heißgas	Ölausgleich				
22,4	MXJ-T3819	MXJ-T3100	9,52	19,05	15,88	6,35	3/8	3/4	5/8	1/4				
28,0				22,22	7/8									
33,6			12,70	25,40	19,10		1/2	1	3/4					
39,2				15,88	28,58			25,40	5/8		1 1/8	1		
44,8			19,10		31,75		28,58	3/4			1 1/4	1 1/8		
50,4					38,10		31,75				1 1/2	1 1/4		
56,0			22,22		44,45		38,10	7/8			1 3/4	1 1/2		
61,6			MXJ-T4422	MXJ-T3800	22,22		44,45	38,10	6,35		7/8	1 3/4	1 1/2	1/4
67,2														
72,8~84,0														
89,6~95,2														
100,8~134,4														
>140,0														

Techn. Änderungen und Irrtum vorbehalten.



WE TURN ON TOMORROW

Exklusiv-Partner für Deutschland

